



ALUMINIUM RAINWATER SYSTEMS

Flowrates Extruded Aluminium Gutters

NOTE: ALL FLOW RATES QUOTED IN LITRES PER SECOND

- Gutter capacities based on BS EN 12056-3:2000, assuming a maximum distance of 50 x gutter depth, from high point to outlet.
- Longer gutters or gutters with corners exceeding 10° will have a reduced capacity.

Profile	Size	63	76	102	76x76	100x76	102x102
Half Round	112	1.12	1.33	1.77	1.66	1.94	2.22
Half Round	125	1.15	1.37	1.82	1.71	2.00	2.28
Half Round	150			-			-
Beaded Deepflow	125x100	2.58	3.68	5.96	4.50	5.70	6.76
Moulded Ogee	100x75	1.16	1.90	-	1.80	2.41	-
Moulded Ogee	125x100	1.28	2.19	3.51	2.66	3.10	-
Moulded Ogee	150x100	-	2.22	3.56	2.70	3.14	4.87
Moulded Ogee	200x150	2.41	3.1	6.07	4.27	5.69	7.59
Box Gutter	100x75	1.62	2.29	4.08	2.87	3.35	4.82
Box Gutter	125x100	1.87	2.65	4.71	3.31	4.42	5.89
Box Gutter	150x100	1.87	2.65	4.71	3.31	4.42	5.89
Box Gutter	150x150	2.29	3.24	5.77	4.60	5.41	7.21
Box Gutter	200x150	2.29	3.24	5.77	4.60	5.41	7.21

For further information contact Stormguard Rainwater Systems Technical Services

Tel: +44 (0)1625 665096
Email: pw@stormguard.co.uk

Stormguard Rainwater Systems pursues a policy of constant product development and information contained within this datasheet is therefore subject to change without notice.